



# Lexmark CX962se

With the new CX962se colour A3 multifunction printer, you get reassuring versatility, exceptional sustainability and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints – up to 45 pages per minute\*. Intuitively navigate the 25 cm colour touchscreen, and save time with single-pass two-sided scanning.

## Print Technology

Colour Laser

## Function

Colour Copying, Colour Printing, Colour Scanning, Trusted Platform Module (TPM), The Trusted Platform Module (TPM) is not available in some countries.

## Workgroup Size

Large Workgroup

## Touch Screen Display

Yes

## Display

Lexmark e-Task 10.1-inch (25.6 cm) colour touch screen

## Print Speed (A4, Black)

Up to 45 ppm<sup>4</sup>

## Print Speed (A4, Colour)

Up to 45 ppm<sup>4</sup>

## Print Speed (A4, Black) Duplex

Up to 45 spm<sup>4</sup>

## Print Speed (A4, Colour) Duplex

Up to 45 spm<sup>4</sup>

## Time to First Page (Black)

As fast as 7.1 seconds

## Time to First Page (Colour)

As fast as 8.2 seconds

## Duplex (2-sided) Printing

Integrated Duplex

## Print Resolution, Black

1200 x 1200 dpi, 4800 Colour Quality

## Print Resolution, Colour

1200 x 1200 dpi, 4800 Colour Quality

## Copy Speed (A4, Black)

Up to 45 cpm<sup>4</sup>

## Copy Speed (A4, Colour)

Up to 45 cpm<sup>4</sup>

## Copy Speed (A4, Black) Duplex

Up to 45 spm<sup>4</sup>

## Copy Speed (A4, Colour) Duplex

Up to 45 spm<sup>4</sup>

## Time to First Copy (black)

As fast as 8.5 seconds

## Time to First Copy (colour)

As fast as 9.5 seconds

## Reduce / Enlarge Range

25 - 400 %

## A4/Ltr Simplex Scan Speed (Mono)

Up to 120/120 sides per minute

## A4/Ltr Simplex Scan Speed (Colour)

Up to 120/120 sides per minute

## A4/Ltr Duplex Scan Speed (Mono)

Up to 240/240 sides per minute

## A4/Ltr Duplex Scan Speed (Colour)

Up to 240/240 sides per minute

## Scan Area, Maximum (mm)

297 x 432 mm

## ADF Scan

DADF (single pass Duplex)

## Scanner Type

Flatbed scanner with automatic document feeder

## Scan Resolution, Enhanced

Up to 600 X 600 dpi

## Scan Resolution, Optical

Up to 600 dpi

## Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF, TXT, RTF, DOCX

## Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer

## Processor Speed

Quad Core, 1.2 GHz

## Memory, Standard

4 GB

## Memory, Maximum

4 GB

## Hard Disk

Intelligent Storage Drive included; Magnetic Hard Disk (optional)

## Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

## Citrix MetaFrame

Microsoft Windows Server 2012 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Foundation running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Essentials running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Standard running Citrix XenApp 6.0, 6.5

## Linux Operating Systems Supported

Ubuntu 20.04, Debian 10, SUSE Linux Enterprise Server 12 SP5, OpenSUSE 15.2, Debian 11, Ubuntu 22.04, Fedora 36, Fedora 37, SUSE Linux Enterprise Server 15 SP4, OpenSUSE 15.4, Red Hat Linux 8.7, Red Hat Linux 9.1

## Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 11

## Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

## Other Operating Systems Supported

Virtually any platform supporting TCP/IP

## Included Paper Handling

550-Sheet Tray, 150-Sheet Multipurpose Feeder, 500-Sheet Output Bin

## Optional Paper Handling

550-Sheet Tray, Offset Stacker, 500-Sheet Staple Offset Finisher, 2 x 550-Sheet Tray, 2000-Sheet Tandem Tray, Cabinet, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, 2,250-Sheet Booklet Staple Hole Punch Finisher

## Paper Input Capacity, Standard

Up to 700 pages 75 gsm bond

## Paper Input Capacity, Maximum

Up to 4,750 pages 75 gsm bond

## Paper Output Capacity, Standard

Up to 500 pages 75 gsm bond

## Paper Output Capacity, Maximum

Up to 2,650 pages 75 gsm bond

## Paper Weight Range Supported - Standard Tray (gsm)

60 - 300 gsm

## Paper Weight Range Supported - Multipurpose Feeder (gsm)

60 - 300 gsm

## A3

Yes

## ADF

300-Sheet Automatic Document Feeder

## ADF Paper Input Capacity

Up to 300 pages 75 gsm bond

## ADF Paper Output Capacity

Up to 300 pages 75 gsm bond

## Finishing Option

Yes

## Finishing Functions

Offset stacking, Stapling, Hole punching

## Number of Paper Inputs, Standard

2

## Number of Paper Inputs, Maximum

6

## Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Speciality Media Guide

## Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A3, A4, A5, B5 Envelope, C4 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Oficio, A6, SRA3, 304.8 x 483 mm

## Standard Ports

USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon

## Optional Local Ports

Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

## Optional Network Ports

MarkNet N8230 Fibre Ethernet Print Server

## Direct USB

Yes

## Ethernet Network

Yes

## Wireless

Yes

## Wireless Network

WPA2™ - Personal, WPA™ and WPA2™ - Personal, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS

## Network Protocol Support

TCP, UDP, IPSEC w/ IPv4, IPSEC w/ IPv6, ICMP, IGMP, IPv4, IPv6

## Network Printing Methods

Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing, Thin Print, LPR

## Network Management Protocols

WINS, APIPA (AutoIP), DHCP, DNS, DDNS, mDNS, ARP, BOOTP

## Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, Certificate Management, SSL Cipher Configuration, TCP/UDP Port Access Control, Security Port Lockdown, TCP Restricted Server List, IPSEC Support (IPv4/IPv6)

## Printable Area (metric)

4 mm of the top, bottom, right and left edges (within)

## Printer Languages (Standard)

PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, PDF 1.7 emulation, PCLm, PCL 5 Emulation

## Fonts and Symbol Sets

39 scalable PPDS fonts, 5 PPDS bitmap fonts, 2 PCL 5/6 bitmap fonts, 163 scalable PostScript fonts, 94 scalable PCL 5/6 fonts

## Laser Cartridge Yields (up to)<sup>3</sup>

, 46,900-page Colour (CMY) Cartridges, 47,700-page Black Cartridge

## Imaging Unit Estimated Yield

Up to 225,000 (black) and 250,000 (colour) pages, based on 5 average letter/A4 size pages per print job and ~ 5% coverage for CS/ CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and ~ 5% coverage for all other printers

## Cartridge(s) Shipping with Product

12,000-page Colour (CMY) Toner Cartridges, 15,000-page Black Toner Cartridge

## Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/](http://www.lexmark.com/) regions for more details.

## Packaged Size (mm - H x W x D)

1080 x 740 x 785 mm

## Packaged Weight, kg

110.5 kg

## Size (mm - H x W x D)

858 x 592 x 660 mm

## Weight

90.1 kg

## Noise Level, Idle

15 dBA

## Noise Level (Print), Operating

50 dBA

## Duplex Print Noise Level, Operating

51 dBA

## Noise Level (Copy), Operating

52 dBA

## Noise Level (Scan), Operating

50 dBA

## ENERGY STAR

Yes

## Average Power (Hibernate Mode)

0.2 watts

## Average Power (Sleep Mode)

1.2 watts

## Average Power (Ready Mode)

67 watts

## Average Power (Printing)

695 watts

## ENERGY STAR Typical Electricity

### Consumption (TEC)

0.69 kilowatt-hours per week

## Product Certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC / KCC Mark, RCM DoC, ErP - EcoDesign, CCC, UKCA DoC, Blue Angel / DE-UZ 219, CECF, CEL, ECMA-370, TED, SIL, TER, UL-AR, GS Mark, ISO-9296, EPEAT Silver, Mopria Certified®

## Maximum Monthly Duty Cycle

Up to 200,000 pages per month<sup>2</sup>

## Recommended Monthly Page Volume

7000 - 50000 Pages<sup>1</sup>

## Specified Operating Environment

Humidity: 15 to 80% Relative Humidity, Altitude: 0 - 2,896 Metres (9,500 Feet), Temperature: 10 to 32.2°C (50 to 90°F)

## Country of Origin

North America & TAA Compliant - Mexico, Rest of World - PRC

## UNSPSC Code

43212110

<sup>1</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

<sup>2</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

<sup>3</sup>Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

<sup>4</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).



| Callout | Availability | Description                                    |
|---------|--------------|------------------------------------------------|
| 1       | Standard     | 25.6 cm (10.1-inch) Colour Touch Screen        |
| 10      | Optional     | Paper Transport Unit                           |
| 11      | Optional     | Folding Paper Transport Unit                   |
| 12      | Optional     | 500-Sheet Staple Finisher                      |
| 13      | Optional     | Offset Stacker                                 |
| 14      | Optional     | 1,250-Sheet Staple Hole Punch Finisher         |
| 15      | Optional     | 2,250-Sheet Booklet Staple Hole Punch Finisher |
| 2       | Standard     | 500-Sheet Output Bin                           |
| 3       | Standard     | 150-Sheet Multipurpose Feeder                  |
| 4       | Standard     | 550-Sheet Tray                                 |
| 5       | Optional     |                                                |
| 6       | Optional     | 2 x 550-Sheet Tray                             |
| 7       | Optional     | 2,000-Sheet Tandem Tray                        |
| 8       | Optional     | Cabinet                                        |
| 9       | Optional     | 1,500-Sheet High-Capacity Tray                 |